

I hereby certify that this paper is being deposited with the United States Postal Service by Express Mail in an envelope addressed to: Asst. Comm. for Patents, Washington, D.C. 20231, on this date.

August 30, 2001
Date

Lalita Nelson
Express Mail Label No.:
EL 846221985 US

ELECTRIC-MOTOR ROTARY POWER TOOL HAVING
A LIGHT SOURCE WITH A SELF-GENERATING POWER SUPPLY

1 The present invention generally relates to rotary power tools, and more
2 particularly to an electric-motor power tool having a light source with a self-generating
3 power supply.

4 Hand-held multipurpose rotary tools are commonly known. These tools
5 generally include an elongated spindle and an electric motor for rotating the spindle at
6 high speeds. A holder is secured to an end of the spindle and is adapted to receive various
7 accessories for striping, sanding, grinding, drilling, cutting and sharpening, for example.

8 Very often the rotary tools are used in places where adequate lighting is not
9 always available. Consequently, the tool operator must work under poor lighting
10 conditions, which may hinder him or her from satisfactorily completing the job, especially
11 when the job requires precision and attention to detail. Brightening the work area with an
12 additional light source such as a lamp or a flashlight can be an inconvenience and/or
13 interfere with the job.

14 It may be possible to incorporate a light source directly into the rotary tools
15 and have it connected to the same power source from which the motor of the tool is
16 supplied. This would require substantially reconfiguring the tool to accommodate the
17 added circuitry of the light source, which would increase the cost of tool manufacture.
18 For rotary tools which are equipped with long and flexible extension attachments, having
19 a light source built into the tool may not be helpful, since the light from the tool would

1 not necessarily illuminate the area in which the work is being performed.

2 Accordingly, it is a primary objective of the present invention to provide an
3 improved rotary power tool having a built-in light source.

4 Another object of the present invention is to provide an improved rotary
5 power tool having a light source with a separate power supply from the power supply of
6 the tool.

7 Still another object of the present invention is to provide such an improved
8 rotary power tool having a light source with a power supply which induces current from a
9 magnet when the magnet is rotated by the power tool.

10 The further object of the present invention is to provide such an improved
11 rotary power tool having a light source which is incorporated into the end of an extension
12 attachment.

13 Yet another object of the present invention is to provide such an improved
14 rotary power tool having a light source that receives its power supply from a current
15 generated from a magnet attached to the extension attachment of the power tool.

16 Other objects and advantages will become apparent upon reading the
17 following detailed description, in conjunction with the attached drawings, in which:

18 FIGURE 1 is a perspective view of a rotary power tool embodying the
19 present invention;

20 FIG. 2 is a sectional view of the area indicated by lines 2-2 of the rotary
21 power tool shown in FIG. 1;

22 FIG. 3 is circuit diagram of a light source in accordance with the present
23 invention;

24 FIG. 4 is a perspective view of a rotary power tool with an extension
25 attachment embodying the present invention;

26 FIG. 5 is a sectional view of the area indicated by lines 5-5 of a light source
27 attachment shown in FIG. 4;

1 FIG. 6 is a side view of an alternate embodiment of the light source
2 attachment in accordance with the invention;

3 FIG. 7 is a front view of the light source attachment of FIG. 6;

4 FIG. 8 is a side view of the light source attachment of FIG. 6, with parts
5 removed for clarity;

6 FIG. 9 is a plan view of an alternate embodiment of a magnet for generating
7 magnetic flux;

8 FIG. 10 is a side view of the magnet shown in FIG. 9.

9 FIG. 11 is a circuit diagram representation of the light source attachment
10 shown in FIG. 6; and,

11 FIG. 12 is a waveform of current produced in the light source attachment of
12 FIG. 6.

13 DETAILED DESCRIPTION

14 The present invention is directed to a multi-purpose rotary power tool which
15 is adapted to receive and hold a number of different tool accessories for various tasks
16 such as striping, sanding, grinding, cutting, drilling and sharpening, for example. The
17 rotary tool includes a built-in light source located near the front of the tool. The power
18 supply for the light source is independent from that of the rotary tool itself, and is
19 generated by a coil of wire which is inductively coupled to a magnet provided in the tool.
20 The magnet spins in conjunction with the spindle in rotary tool, in close proximity to the
21 stationary wire coil (also known as a choke or inductor in the art). As the magnet spins,
22 the magnet's flux lines pass through the wire coil, inducing a current in the coil. As long
23 as the light source is connected to the coil, current flows to the light source, which could
24 be, for example, a light emitting diode (LED).

25 Broadly stated, the present invention is directed to a rotary power tool
26 having a light source, and includes a housing, an electric motor provided in the housing
27 and an elongated spindle engaged with and adapted to be rotatably driven by the motor.

1 A rotatable holding assembly is attached to an end of the spindle and extends from a front
2 end of the housing for holding a tool accessory. At least one magnet is adapted to be
3 rotated by the spindle for producing a magnetic field, and a generally tubular sleeve is
4 attached to the front end of the housing. At least one light emitting diode projects from a
5 front end of the sleeve, generally between the inner and the outer surfaces of the sleeve.
6 An inductive coil is also imbedded at least partially in the sleeve generally between the
7 inner and the outer surfaces, proximate the magnet for generating an electric current from
8 the magnetic field. Electrical conductors are also embedded and routed through the
9 sleeve for supplying the electric current from the inductive coil to the light emitting diode.

10 The invention is also directed to a light source apparatus for an electric-
11 motor rotary power tool having a rotatable tool holder assembly and equipped to receive
12 an accessory attachment. The light source apparatus includes a magnet constructed and
13 adapted to be removably secured to the rotatable tool holder assembly, and a generally
14 tubular sleeve which is configured and adapted to be removably attached to a portion of
15 the power tool configured for receiving the accessory attachment. A current generating
16 device is at least partially imbedded in the sleeve generally between the inner and the
17 outer surfaces of the sleeve, and positioned proximate the magnet when the sleeve is
18 attached to the power tool, for generating an electric current from a magnetic field created
19 by the magnet when the power tool is operated. Lighting devices project from a front end
20 of the sleeve and is adapted to illuminate when supplied with the electric current from the
21 current generating device. Electrical conductors routed through the sleeve between the
22 inner and the outer surfaces supply the electric current from the current generating device
23 to the lighting device.

24 Turning now to FIG. 1, the rotary power tool of the present invention is
25 indicated generally at 10 and includes a housing 12, a light source attachment 14, a tool
26 accessory holder assembly 16 and a tool accessory 18. A pair of light emitting diodes
27 (LEDs) 20 are included in the light source attachment 14 for illuminating the area
28 surrounding the tool accessory 18. The rotary tool 10 is AC powered as indicated by a

1 power cord 22. However, it may also be battery operated. The tool accessory 18 shown
2 in Fig. 1 is only one example, and any number of known tool accessories can be used in
3 its place.

4 Turning to FIG. 2, the rotary tool 10 further includes an electric motor 24
5 (AC or battery powered) for rotating a shaft or spindle 26 about its longitudinal axis. The
6 tool accessory holder assembly 16 includes a hollow, generally cylindrical base portion 28
7 which slips over the end of the spindle 26 opposite the motor 24 to securely mount the
8 accessory holder assembly onto the spindle. A threaded head portion 30 extends from the
9 base portion 28. A collet 32 is inserted into the hollow of the head portion 30, and a
10 collet nut 36 is threaded onto the head portion 30 to enable the collet 32 to securely grab
11 the tool accessory 18 inserted into the collet in a conventionally known manner.

12 A front end 34 of the housing 12 is threaded to receive various attachments
13 that are constructed and adapted to be used with the rotary power tool 10, for example, a
14 router attachment, a cutting attachment, a sharpening attachment, an extension
15 attachment, etc. In accordance with one embodiment of the present invention, the light
16 source attachment 14 is likewise constructed and adapted to be threaded onto attachment
17 threads 38 at the front end 34 of the housing 12.

18 The light source attachment 14 includes a substantially tubular sleeve 39
19 having an inner circumferential surface 40 and an outer circumstantial surface 41. The
20 inner circumferential surface 40 is threaded to cooperatively receive the threaded front
21 end 34 of the housing 12. Each of the two LEDs 20 are imbedded in the sleeve 39
22 generally between the inner and the outer circumferential surfaces 40, 41, and projects
23 from the front end of the sleeve 39 towards the tool accessory 18 (shown in FIG. 1), so as
24 to illuminate the intended work area. The LEDs 20 are connected to a pair of wire
25 conductors 42, which are also connected to a coil of wire or inductive coil 43 to complete
26 an electrical circuit. The wire conductors 42 and the inductive coils 43 are provided
27 within the thickness of the sleeve 39 and generally from the front to the back. In other
28 words, the LEDs 20, the inductive coils 43 and the wire conductors are embedded in the

1 sleeve 39 generally between the inner and the outer surfaces 40, 41, to form a single
2 integrated piece, which simplifies implementation with the power tool 10.

3 A magnet ring 44 with at least two poles is secured to the base portion 28 of
4 the tool accessory holder assembly 16 proximate the inductive coils 43, and rotates
5 synchronously with the base portion 28 and the spindle 26 when the rotary tool 10 is
6 operated. Those skilled in the art will recognize that instead of a ring, the magnet 44 can
7 also be one or more individual magnets attached along the diameter of the base portion
8 28.

9 In the preferred embodiment, the sleeve 39 is formed from an easily
10 moldable, nonelectrically conductive plastic or like material, and the LEDs 20 are
11 Infineon Technologies Hyper-Bright LEDs. However, other light sources are
12 contemplated, such as super bright white LEDs and incandescent light bulbs. Moreover,
13 the light source attachment 14 may include only one LED 20, or more than two. The
14 preferred inductive coil 42 is a Siemens B82144-A2107-J. However, many other similar
15 inductive coils are contemplated.

16 FIG. 3 depicts an electrical circuit representation of the light source
17 attachment 14 of the present invention. In operation, as the magnet ring 44 is rotated
18 about the longitudinal axis of the spindle 26, either in a clockwise or a counterclockwise
19 direction, electric current is induced in the coil 43 and supplied to the LED 20. The
20 current causes the LED 20 to illuminate each half cycle when the LED is forward biased,
21 as shown by an arrow 46. In FIG. 3, the magnet ring 44 is shown to have four poles. It
22 should be understood however that magnetic ring 44 may have two or more poles,
23 depending on the required characteristics in the final configuration of each different
24 application.

25 Turning now to FIG. 4, the power tool 10 is shown with an extension
26 attachment 48 connected to the front end 34 of the housing 12. The extension attachment
27 48 allows the user to reach into places not easily accessible by the tool 10 itself. Included
28 in the extension attachment 48 are a connection portion 50, an extension portion 52, and a

1 handpiece portion 54. A flexible shaft 56 (shown in FIG. 5) is routed coaxially and along
2 the length of the extension attachment 48. The extension attachment 48 connects to the
3 tool 10 at the connection portion 50, which is constructed and adapted to be threaded onto
4 the attachment threads 38 in the housing 12 (best shown in FIG. 2). When the extension
5 attachment 48 is connected to the tool 10, the flexible shaft 56 transfers the rotation of the
6 spindle 26 in the power tool 10 (shown in FIG. 2) to an accessory holder assembly 60 at a
7 front end 58 of the handpiece portion 54.

8 Referring to FIG. 5, the handpiece portion 54 is shown, and includes the
9 accessory holder assembly 60 and a light source attachment 62 which are constructed
10 similarly to the accessory holder assembly 16 and the light source attachment 14 shown in
11 FIG. 2. The accessory holder assembly 60 is configured and adapted to be attached to the
12 flexible shaft 56, and the light source attachment 62 is configured and adapted to be
13 screwed onto a threaded portion 64 formed at the front end 66 of the handpiece portion
14 54. The light source attachment 62 includes (similar to the light source attachment 14
15 described above) a generally tubular sleeve 67 which is threaded on an inner surface 68 to
16 cooperatively screw onto the threaded portion 64 of the hand piece portion 54. A pair of
17 LEDs 69 project from the sleeve 67 near the accessory holder assembly 60, and are at
18 least partially imbedded in the sleeve 67 between the inner surface 68 and an outer
19 surface 70. Each LED 69 is electrically connected to an inductive coil 71 formed in the
20 the sleeve 67 between the inner and the outer surfaces. When the light source attachment
21 62 is attached to the threaded portion 64, the inductive coils 71 become positioned
22 proximate a magnet 72, which is fixed to a base 74 of the accessory holder assembly 60.

23 Similar to the description given above with respect to the LEDs 20, the
24 LEDs 69 are illuminated when the rotary tool 10 is operated and the rotation of the
25 spindle 26 in the rotary tool is transferred to the flexible shaft 56, thereby rotating the
26 magnet ring 72. The rotating magnet ring 72 induces a current in the coils 71, which is
27 supplied to the LEDs 69. This arrangement allows the light from the LEDs 69 to be

1 focused in the area front of the accessory holder assembly 60, where the light is most
2 desirable.

3 Turning now to FIGS. 6-8 and in accordance with another embodiment of
4 the present invention, a light source attachment 76 for the extension attachment 48
5 includes a generally tubular sleeve 78 that is constructed and adapted to be screwed onto
6 the threaded portion 64 formed at the front end 66 of the handpiece portion 54 (best
7 shown in FIG. 7). A pair of LEDs 80 project from the sleeve 78 near the accessory holder
8 assembly 60 and are connected in parallel with an inductive coil 82, which is also partially
9 imbedded in the sleeve 78 near the accessory holder assembly. The wires connecting the
10 LEDs 80 with the inductive coil 82 are also imbedded within the sleeve 78. As in the
11 light source attachments 14 and 16 described above, the LEDs 80, the inductive coil 82
12 and the wires that connect them are at least partially imbedded in an easily moldable
13 plastic type material for ease of manufacture and implementation with the power tool 10
14 or the extension attachment 48.

15 For generating current in the inductive coil 82, a magnet ring 84 is slipped
16 onto the base portion 86 of the accessory holder assembly 60 that is outside the front end
17 58 of the hand piece portion 54, and secured by a jam nut 88, which screws onto a
18 threaded head portion 90 of the accessory holder assembly (best shown in FIG. 8) . The
19 magnetic ring 84 may also be secured by a collet nut 92 (best shown in FIG. 6) instead of
20 the jam nut 88. This arrangement allows the light source attachment 76 to be easily
21 incorporated into the existing extension attachment 48 by the tool operator, without the
22 needs to retrofit the extension attachment at the factory or by a technician.

23 As an alternative to the magnet ring 84/jam nut 88 arrangement described
24 above, and referring to FIGS. 9 and 10, an inside opening 94 of a generally annular
25 magnet 96 is constructed and configured to matingly attach to an outer hexagonal surface
26 98 of a nut 100. The inner opening 102 of the nut 100 is constructed and adapted to be
27 threaded onto the head portion 90 of the accessory holder assembly 60 and tightened
28 against the base portion 86. The nut 100 extends slightly beyond an inner surface 102 of

1 the magnet 96 so as to prevent the magnet, which is relatively brittle, from coming in
2 contact with the base portion 86. The nut 100 is also configured to extend sufficiently
3 beyond an outer surface 104 of the magnet 96 to enable a tool to tighten or loosen the nut
4 against or from the base portion 86 of the accessory holder assembly 60. Those of
5 ordinary skill in the art will recognize that the outer surface 98 of the nut 100 can have
6 shapes other than hexagonal that allow the nut to be tightened and loosened by a suitable
7 tool.

8 The light source attachment 76 is also adapted to be operatively connected
9 directly to the rotary tool 10. In this case, the sleeve 78 would be screwed onto the
10 threads 38 in the housing 12, and the magnet ring 84 would be slipped onto the part of the
11 base portion 28 that extends outside the front end 34 of the housing 12 (best shown in Fig.
12 2). The magnet ring 84 can either be secured by the jam nut 88 or the collet nut 36. The
13 magnet 96/nut 100 arrangement is also adapted to be secured directly to the rotary tool 10.
14 The magnet 96 would be secured onto to the base portion 28 by the threaded inner
15 opening 102 of the nut 100. When the sleeve 78 and the magnet ring 84 (or the magnet
16 96) is secured onto either the handpiece portion 54 or the rotary tool 10 itself, the
17 inductive coil 82 and the magnet ring 84 are positioned proximate each other as shown in
18 FIGs. 6 and 7.

19 As shown in FIG. 11, the magnet ring 84 (or the magnet 96) preferably has
20 4 poles, and accordingly, flux lines 106 extending from the North to South poles. When
21 the magnet ring 84 (or the magnet 96) spins in close proximity to the inductive coil 82,
22 current is induced in the inductive coil as the flux lines 106 pass alternately through it. As
23 the poles pass by the inductive coil 82, they generate a positive or negative current in the
24 inductive coil, depending on the pole which is in proximity. The current waveform
25 shown in FIG. 10 is the result of this process. The two LEDs 80 are connected so that
26 their polarities are opposite, and since each LED 80 allows current to flow in only one
27 direction, they switch on and off alternately. As long as the frequency of the switching is
28 greater than that which the human eye can detect, each LED 80 will appear to be on

1 constantly when the tool 10 is being operated. This frequency is controlled by the number
2 of magnetic pole pairs and the frequency at which they pass by the inductive coil 82.
3 Accordingly, the rotational speed of the tool 10, and thus, the magnetic ring 84 (or the
4 magnet 96) controls the frequency.

5 From the foregoing description, it should be understood that an improved
6 electric-motor rotary power tool has been shown and described which has many desirable
7 attributes and advantages. It is provided with a light source which illuminates the area
8 where the tool is intended to be used. The light source is supplied with a current which is
9 generated from the rotation of the spindle of the tool, and therefore, does not require
10 tapping into the power source of the tool itself. This simplifies the circuitry within the
11 tool and does not drain the power source of the battery operated power tools.

12 While various embodiments of the present invention have been shown and
13 described, it should be understood that other modifications, substitutions and alternatives
14 are apparent to one of ordinary skill in the art. Such modifications, substitutions and
15 alternatives can be made without departing from the spirit and scope of the invention,
16 which should be determined from the appended claims.

17 Various features of the invention are set forth in the appended claims.